



36
kWh/1000h

A
energy class

75
lumens/watt

Biax™ T 2-pin with Amalgam, Internal Starter

F32W TBX/T4/840/A/4P TU
93112574

Product information

Ultra compact energy saving CFL lamps with triple-tube design give an ideal light source for small fixtures and downlighters. Biax™ T lamps allow more compact fixture designs with the same lumen output as Biax™ D lamps. They can also be used to deliver higher lumen output from existing designs. The Biax™ T & T/E lamps are electrically interchangeable with Biax™ D and D/E lamps. They are available in 13, 18, 26, 32 and 42W. Light output ranges between 900 and 3200 lumens. Biax™ T/E lamps with a 4-pin electrical connection and without an internal starter are designed for high-frequency electronic ballasts. The use of separate electronic ballasts makes them suitable for almost every kind of energy supply: high and low voltages, accumulators, batteries, solar cells and systems that can be dimmed.



Product data

Product Code	93112574
Bulb Shape	Hex plug-in
Bulb maximum overall diameter [mm]	49.3
Net weight per piece [g]	88
Gross weight per piece [g]	125
Operating position	U - Universal
UV radiance	exempt
Brand	Tungsrám
Cap/Base	GX24q-3

Performance data

Colour Code	840
Rated Lumens [lm]	2400
Weighted energy consumption [kWh/1000h]	35.2
Energy efficiency class (EEC)	A
Rated Life [h]	12000
Rated median life on electronic (HF / ECG) ballast on IEC 12-hour cycle	20000
Rated median life on electronic (HF / ECG) ballast on IEC 3-hour cycle	17000
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	2400
Colour Rendering Index (CRI) [Ra]	82

Electrical data

Rated power [W]	32.0
Operating Temperature (MIN) [°C]	-15
Starting ambient temperature range	-15
Dimming Capability	Yes
Nominal power [W]	32
Nominal lamp voltage [V]	100

Logistic data

Shipment	Standard
DUN Code	15994100031212
EAN Code	5994100031215
Pack Quantity	10
Inner pack type	BOX
Layer quantity	320 EUR
Layer quantity EUR	320
Pallet quantity EUR (PC)	1920
Outer case size	262 x 108 x 166 (mm)
Product status	Available