

ToLEDo GLS

ToLEDo GLS V6 806LM 865 E27 SL

0026629



Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent GLS lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating



NOTES

undefined

PRODUCT OVERVIEW

| | |
|-----------------------------|-------------------------------------|
| Product name | ToLEDo GLS V6 806LM 865 E27 SL |
| Technology | LED |
| Watt (Rated) (W) | 8.5 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer |
| ETIM Class | EC001959 |
| E-number FI | 4740502 |
| Warranty | 3 years |
| Useful luminous flux (Fuse) | 806 |
| Luminous flux (lm) | 806 |
| Colour temperature (K) | 6500 |
| Light colour | Daylight |
| CRI (Ra) | 80 |
| Beam Angle (°) | 180 |
| Power consumption (W) | 8.5 |
| Wattage (W) | 8.5 |
| Average life (Nominal) (h) | 15000 |
| Product EAN number | 5410288266299 |

DATA TABLE

General data

| | |
|---------------------|-------------------------------------|
| Product name | ToLEDo GLS V6 806LM 865 E27 SL |
| Technology | LED |
| Watt (Rated) (W) | 8.5 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer |

ToLEDo GLS

ToLEDo GLS V6 806LM 865 E27 SL

0026629

| | |
|---|----------|
| Performance ambient temperature Tq (°C) | 25 |
| ETIM Class | EC001959 |
| E-number FI | 4740502 |
| Warranty | 3 years |

Optical data

| | |
|--|----------|
| Useful luminous flux (Fuse) | 806 |
| Luminous flux (lm) | 806 |
| Luminous flux (Rated) (lm) | 806 |
| Colour temperature (K) | 6500 |
| Light colour | Daylight |
| CRI (Ra) | 80 |
| Beam Angle (°) | 180 |
| Lumen maintenance at end of nominal life (%) | 70 |

Electrical data

| | |
|---|---------|
| Power consumption (W) | 8.5 |
| Wattage (W) | 8.5 |
| Starting time (max) (s) | 0.5 |
| Warm-up time to 60% of full light (max) (s) | 1 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 0.5 |
| No. Of switching cycles before premature failures | >50000 |
| Inrush Current (A) | 2.4 |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 173 |
| Max. products per 16A C Breaker | 278 |
| Max. products per 20A C Breaker | 348 |

Lifetime data

| | |
|----------------------------|-------|
| Average life (Nominal) (h) | 15000 |
| Average life (Rated) (h) | 15000 |

Physical data

| | |
|-------------------------------|-------|
| Nominal Product Length (mm) | 112 |
| Nominal Product Diameter (mm) | 60 |
| Weight (kg) | 0.053 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5410288266299 |
| Packaging single length / height (cm) | 11.3 |
| Packaging single width (cm) | 6.4 |
| Packaging single depth (cm) | 6.4 |
| DUN14 (inner) | 25410288266293 |

ToLEDo GLS

ToLEDo GLS V6 806LM 865 E27 SL

0026629

| | |
|--------------------------------------|----------------|
| Units per inner package | 6 |
| Packaging inner length / height (cm) | 20.4 |
| Packaging inner width (cm) | 13.4 |
| Packaging inner depth (cm) | 13.7 |
| DUN14 (outer) | 15410288266296 |
| Units per outer package | 60 |
| Packaging outer length / height (cm) | 72.4 |
| Packaging outer width (cm) | 22.2 |
| Packaging outer depth (cm) | 29.7 |

Safety data

| | |
|-------------------------------------|--|
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Dry applications use only | Yes |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |

TECHNICAL DRAWINGS

