

PRODUCT DATASHEET HO 80 W/830

LUMILUX® T5 HO | Tubular fluorescent lamps 16 mm, high output, with G5 base



Areas of application

- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks
- Outdoor applications only in suitable luminaires

Product benefits

- Up to 20 % more economical than LUMILUX® T8

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable




TECHNICAL DATA

Electrical data

| | |
|----------------------|---------|
| Nominal wattage | 80 W |
| Construction wattage | 80.40 W |
| Nominal voltage | 152 V |
| Nominal current | 0.53 A |

Photometrical data

| | |
|---------------------------|--------------------|
| Luminous flux | 7000 lm |
| Luminous efficacy | 87 lm/W |
| Luminous flux at 35 °C | 7000 lm |
| Light color (designation) | LUMILUX Warm White |
| Color temperature | 3000 K |
| Color rendering index Ra | ≥80 |
| Light color | 830 |
| Rated LLMF at 2,000 h | 0.95 |
| Rated LLMF at 4,000 h | 0.93 |
| Rated LLMF at 6,000 h | 0.92 |
| Rated LLMF at 8,000 h | 0.90 |
| Rated LLMF at 12,000 h | 0.90 |
| Rated LLMF at 16,000 h | 0.90 |
| Rated LLMF at 20,000 h | 0.89 |



Dimensions & Weight

| | |
|---|------------|
| Overall length | 1463.20 mm |
| Length with base excl. base pins/connection | 1449 mm |
| Diameter | 16,0 mm |

| | |
|----------------|----------|
| Tube diameter | 16 mm |
| Product weight | 116.45 g |

Lifespan

| | |
|--|-----------------------|
| Lifespan | 24000 h |
| Service life | 19000 h ¹⁾ |
| Rated lamp survival factor at 2,000 h | 0.99 |
| Rated lamp survival factor at 4,000 | 0.99 |
| Rated lamp survival factor at 6,000 | 0.99 |
| Rated lamp survival factor at 8,000 h | 0.99 |
| Rated lamp survival factor at 12,000 h | 0.99 |
| Rated lamp survival factor at 16,000 | 0.97 |
| Rated lamp survival factor at 20,000 h | 0.85 |
| Lifespan B50 | 24000 h |

¹⁾ With preheat ECG

Additional product data

| | |
|-----------------------------|--|
| Base (standard designation) | G5 |
| Mercury content | 2.0 mg |
| Product remark | Suitable for ECG operation only / Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C |

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | G |
| Energy consumption | 81.00 kWh/1000h |

Country-specific categorizations

| | |
|-----------------|----------------------------|
| ILCOS | FDH-80/830-L/P/-G5-16/1449 |
| Order reference | HO 80W/830 |

Energy labelling regulation data acc EU 2019/2015




| | |
|--------------------------------|-----------|
| Lighting technology used | LFL_T5_HO |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |

| | |
|---|--------------|
| Light source cap-type (or other electric interface) | G5 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 1463.20 mm |
| Height | 16,0 mm |
| Width | 16,0 mm |
| Chromaticity coordinate x | 0,440 |
| Chromaticity coordinate y | 0,403 |
| Beam angle correspondence | SPHERE_360 |

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|-------------------------------|
|  | Certificates |
|  | Certificates |
|  | Declarations Of Conformity CE |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4050300515137 | Unpacked 1 | 1,462 mm x 15 mm x 15 mm | 115.00 g | 0.33 dm ³ |
| 4050300591827 | Sleeve 1 | 1,464 mm x 18 mm x 18 mm | 138.00 g | 0.47 dm ³ |
| 4050300515144 | Shipping box 40 | 1,496 mm x 199 mm x 87 mm | 5182.00 g | 25.90 dm ³ |

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4050300591834 | Shipping box 20 | 1,511 mm x 104 mm x 88 mm | 3058.00 g | 13.83 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.