



TATANKA

AR4P16 – Cod. 83108273i

Digitaler Keramik-Turmheizlüfter mit Oszillationsfunktion und Touch-Bedienfeld – sicher und effizient. 2 Heizstufen: 1.400/2.000 W. Sommerlüftungsfunktion. Regelbares elektronisches Thermostat. Fernbedienung. 24-Stunden-Timer. LED-Display mit Temperaturanzeige. Kippschutzschalter.



TATANKA | AR4P16 – Cod. 83108273i



Resa in m ³ – Suitable for cubic meters	60
(v)	220-240
(Hz)	50-60
Leistung (W)	2000
Leistungsstufen (W)	1400/2000
Sommerbelüftung	•
Horizontale Schwingung	•
Verstellbares elektronisches Thermostat	•
Timer [hh] (On)/(off)/(on+off)/(progr.)	24 (off)
Touch-Bedienelemente	•
Display	•
Fernbedienung	•
Kippschutz	•
Überhitzungsschutz	•
Tragegriff	•
Nettogewicht (kg)	1,9
Bruttogewicht (kg)	2,65
Produktmaße LxPxH (cm)	21 x 21 x 63,5
Imballo singolo – Giftbox (cm)	18 x 15 x 67
EAN CODE (1 pz – 1 pcs)	8004032114089
Pezzi per pallet – Pcs per Pallet	60

Dieses Produkt ist nur für gut isolierte Räume oder für den gelegentlichen Gebrauch geeignet.



HEIZUNG

Ardes

Aria di casa



EN

Information requirements for electric local space heaters – REGULATION (EU) 2024/1103

Model identifier(s):		AR4PI6			
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat output/room temperature control (select one)	
Nominal heat output	P _{nom}	2,000	kW	Single stage heat output and no room temperature control	no
Minimum heat output (indicative)	P _{min}	1,400	kW	Two or more manual stages, no room temperature control	no
Maximum continuous heat output	P _{max,c}	2,000	kW	With mechanic thermostat room temperature control	no
Power consumption				With electronic room temperature control	yes
In off mode	P ₀	N.A.	W	Electronic room temperature control plus day timer	no
In standby mode	P _{sm}	0,3	W	Electronic room temperature control plus week timer	no
In idle mode	P _{idle}	0,3	W	Other control options (multiple selections possible)	
In network standby	P _{nsm}	N.A.	W	Room temperature control, with presence detection	no
Standby mode with display of information or status			no	Room temperature control, with open window detection	no
Seasonal space heating energy efficiency in active mode	η _{s,on}	91,5	%	With distance control option	no
				With adaptive start control	no
				With working time limitation	yes
				With black bulb sensor	no
				Self-learning functionality	no
				Control accuracy	no
Contact details	B&B TRENDS ITALIA s.r.l. – via Sottocorna 21/B, 24020 Parre (BG) – Italy				