TUNGSRAM

Innovation is our heritage EST. 1896





LED Stik G5 LED14/STIK/840/220-240V/E27/F 2/10 93120147

Product information

LED Stik illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years*. That's a long time you can spend not worrying about light bulbs.

Features & benefits

- LED technology for energy saving
- Redesigned shape with multiple advantages:
- To fit in more fixtures compared to CFL
- Optimised for omni-directional light distribution
- Space-saving benefits on-shelf
- 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W bulb
- Rated life of 15 years*
- 3 colour options 3000K, 4000K & 6500K
- Always ready instant brightness
- No mercury worry-free use and disposal
- Warranty: 2 years with maximum 8 000 burning hours



LED Stik G5 LED14/STIK/840/220-240V/E27/F 2/10 93120147

according to Tungsram Standard Warranty conditions

• Based on 2.7 hours of per day use.

Application areas









Product data

Product description LED14/STIK/840/220-240V/E27/F 2/10 Nominal Length [mm] 137 Net weight per piece [g] 75 Dimmability No Brand Tungsram Cap/Base E27	Product Code	93120147
Net weight per piece [g]75DimmabilityNoBrandTungsram	Product description	LED14/STIK/840/220-240V/E27/F 2/10
Dimmability No Brand Tungsram	Nominal Length [mm]	137
Brand Tungsram	Net weight per piece [g]	75
	Dimmability	No
Cap/Base E27	Brand	Tungsram
	Cap/Base	E27

Performance data

Color consistency (SDCM)	6	
Rated efficacy [lm/W]	114.29	
Energy efficiency class (EEC)	Е	
Rated life L70/B50 [h]	15 000	
Input Frequency [Hz]	50/60	
Nominal correlated colour temperature (CCT) [K]] 4000		
Nominal lumens [lm]	1600	
Colour Rendering Index (CRI) [Ra]	80	

Electrical data

Nominal lamp power factor	0.7
Operating Temperature (MIN) [°C]	-10
Operating Temperature (MAX) [°C]	40
Starting time (sec)	0.5
Number of switching cycles	30 000
Nominal lamp voltage range [V]	220-240
Nominal power [W]	14



Logistic data

Shipment	Standard
DUN Code	15994100085956
EAN Code	5994100085959
Pack Quantity	2/10
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)
Link to EPREL (HTTP)
Datasheet (PDF)
Images (HTTP)
Declaration of Conformity (PDF)